

Manufacturer's declaration

ASSA ABLOY, the global leader
in door opening solutions.












EC assurance of conformity

In compliance to directive 89/106/EEC, CPD (Construction Products Directive) amended by directive 93/68/EEC of the Council of European Communities of 22 July 1993; product

Locks and latches- Mechanically operated locks, latches and locking plates

Name of manufacturer: ASSA OEM AB
Type of product: Lock case
Name: Assa
Type: 221-35/50/70

Lock case performance:

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 |
|---|---|---|---|---|---|---|--|---|---|---|
|  |  |  |  |  |  |  |  |  |  |  |
| 3 | X | 9 | 1 | 0 | F | 2 | B | B | 3 | 0 |

| Box | Classification | Explanation of performance | Range |
|-----|--------------------------------------|--|---------|
| 1 | Category of use | For public use, high chance of misuse | (1-3) |
| 2 | Durability | 200.000 cycles, 120N on latchbolt | (A-X) |
| 3 | Door mass and closing force | Above 200 kg door mass, 15N close force | (1-9) |
| 4 | Fire/smoke resistance | For use on fire/smoke resistant door | (0-1) |
| 5 | Safety | No safety requirement | (0) |
| 6 | Corrosion and temperature resistance | High corrosion resistance (96h saltspray). | (0,A-G) |
| 7 | Security and drill resistance | Low security, no drill resistance | (1-7) |
| 8 | Field of door application | Hinged door | (A-R) |
| 9 | Type of key and locking operation | Cylinder lock or latch, automatic locking | (0,A-H) |
| 10 | Type of spindle operation | Lock or latch without follower | (0-4) |
| 11 | Key identification requirement | Not applicable | (0,A-H) |

Manufacturer declares that above mentioned product fulfils conformity of following standards, quality systems and marking.

Standards conformity

EN 12209:2004
 Type testing by manufacturer to SS-EN/IEC 17025
 EC- Certificate of conformity 1162-CPD-0233
 SS 3522 issue 3



Quality conformity

Manufacturers' quality system to EN 9001 with independent quality assessment
 Manufacturers' system to EN 14001 with independent quality assessment



(DNV: 98-SKM-AQ-019)
 (DNV: 98-SKM-AE-037)

Marking of lock case

None

CE marking compulsory



Marking not applicable



Quality label

The product must be installed and used according to given instructions and norms. Any alteration on the product is prohibited without the consent of the manufacturer. If so, the manufacturer will no longer take responsibility for the function of the product.

Eskilstuna, 4 May 2009



Productmanager Mechanical Lock case.
 ASSA OEM AB