

## Manufacturer's declaration

ASSA ABLOY, the global leader

Locks and latches- Mechanically operated locks, latches and locking plates

Name of manufacturer:

Type of product:

Name:

ASSA OEM AB

Lock case

Assa

**Type:** 231-35/50/70

Lock case performance:

1	2	3	4	5	6	7	8	9	10	11
	B	kg		<b>3</b>		<del>Q</del>		The state of the s	8	€ <sup>®</sup>
3	X	9	0	0	F	2	В	В	0	0

<u>Box</u>	<u>Classification</u>	Explanation of performance	Range
1	Category of use	For public use, high chance of misuse	(1-3)
2	Durability	200.000 cycles, 120N on latchbolt	(A-X)
3	Door mass and closing force	Above 200 kg door mass, 15N close force	(1-9)
4	Fire/smoke resistance	For non use on fire/smoke resistant door	(0-1)
5	Safety	No safety requirement	(0)
6	Corrosion and temperature resistance	High corrosion resistance (96h saltspray).	(0,A-G)
7	Security and drill resistance	Low security, no drill resistance	(1-7)
8	Field of door application	Hinged door	(A-R)
9	Type of key and locking operation	Cylinder lock or latch, automatic locking	(0,A-H)
10	Type of spindle operation	Lock or latch without follower	(0-4)
11	Key identification requirement	Not applicable	(0,A-H)

Manufacturer declares that above mentioned product fulfils conformity of following standards, quality systems and marking.

Standards conformity EN 12209:2004 /AC 2005 ex Type testing by manufacture Certificate of conformity 158 SS 3522 issue 3				
<b>Quality conformity</b> Manufacturers' quality system Manufacturers' system to EN	$\boxtimes$	(DNV: 98-SKM-AQ-019) (DNV: 98-SKM-AE-037)		
Marking of lock case None  C € marking compulsory Quality label		Marking not applicable	$\boxtimes$	

The product must be installed and used according to given instructions and norms. Any alteration on the product is prohibited without the consent of the manufacturer. If so, the manufacturer will no longer take responsibility for the function of the product.

Eskilstuna, 5 May 2009

**ASSA OEM AB** 

Productmanager Mechanical Lock case. ASSA OEM AB