

Manufacturer's declaration

ASSA ABLOY, the global leader

Locks and latches- Mechanically operated locks, latches and locking plates

Name of manufacturer: ASSA OEM AB Type of product: Lock case Name: Assa Type: 313

Lock case performance:

1	2	3	4	5	6	7	8	9	10	11
	M	kg		**			B	The state of the s	R	
3	X	9	0	0	F	3	В	A	3	0

<u>Box</u>	Classification	Explanation of performance	<u>Range</u>
1	Category of use	For public use, high chance of misuse	(1-3)
2	Durability	200.000 cycles, 120N on latchbolt	(A-X)
3	Door mass and closing force	Above 200 kg door mass, 15N close force	(1-9)
4	Fire/smoke resistance	For non use on fire/smoke resistant door	(0-1)
5	Safety	No safety requirement	(0)
6	Corrosion and temperature resistance	High corrosion resistance (96h saltspray).	(0,A-G)
7	Security and drill resistance	Medium security, no drill resistance	(1-7)
8	Field of door application	Hinged door	(A-R)
9	Type of key and locking operation	Cylinder lock or latch, manually locking	(0,A-H)
10	Type of spindle operation	Lock or latch for heavy duty unsprung op.	(0-4)
11	Key identification requirement	Not applicable	(0,A-H)

Manufacturer declares that above mentioned product fulfils conformity of following standards, quality systems and marking.

Standards conformity				
EN 12209:2004 /AC 2005 ex	cluding Annex ZA		\boxtimes	
Type testing by manufacture	\boxtimes			
Certificate of conformity NO	$\overline{\boxtimes}$			
SS 3522 issue 3				
Quality conformity				
Manufacturers' quality syster	\boxtimes	(DNV: 98-SKM-AQ-019)		
Manufacturers' system to EN	\boxtimes	(DNV: 98-SKM-AE-037)		
Marking of lock case				
None				
← marking compulsory	\boxtimes	Marking not applicable		
Quality label	_	3	_	

The product must be installed and used according to given instructions and norms. Any alteration on the product is prohibited without the consent of the manufacturer. If so, the manufacturer will no longer take responsibility for the function of the product.

Eskilstuna, 8 May 2009

Productmanager Mechanical Lock case.

ASSA OEM AB

ASSA OEM AB Tfn: +46-16-17 70 00 Fax: +46-16-17 70 86